Augmentation of Nano Fluid (γ - Al_2O_3 /Water) Heat Transfer with Different Forms of Twisted Tape in a Horizontal Tube

¹Riyadh S. Al-Turaihi and ²Sarah H. Oleiwi

¹Department of Mechanical Engineering, University of Babylon, Hilla, Iraq

²Department of Mechanical Engineering, University of Al-Qadisiyah, Al-Diwaniya, Iraq

Abstract: Twisted tapes are used to rise the amount of the heat transfer in pipes. In this study, the heat transfer was studied numerically in horizontal pipe with normal twisted tape inserted and two modified twisted tapes. Nine different values of fluid velocity were used (0.15, 0.2, 0.25, 0.3, 0.6, 0.65, 0.9, 0.95 and 1.3 m/sec), the flowing fluid through the pipes was γ - Al_2O_3 /water nanofluid. ANSYS Fluent 15.0 combined with k-epsilon turbulent model was used for simulations, the model was validated using the classical formula of Dittus-Boelter. The results from the simulations were established to be in good agreement with the formula results.

Key words: ANSYS Fluent, heat transfer, nano fluid, numerical study, twisted tapes, simulations

INTRODUCTION

The heat transfer coefficient is an important character to consider. Heat transfer technology enhancement has become very important for industrial applications counting nuclear power stations, heat exchangers and solar water heater as well as in processes such as petroleum and chemical engineering (Hong *et al.*, 2017). Massive effective heat transfer area should be used to increase the heat transfer in addition to the residence time should increase, turbulent intensity should improve and the boundary layer should have developed (Hong *et al.*, 2017). Twisted tapes were used for the heat exchangers to facility the recovery of heat from the diesel exhaust generator (Mokkapati and Lin, 2014) numerically studied the recovery of heat from the exhaust generator for heat exchangers using twisted tape inserted through a corrugated tube. They found an increase in the heat transfers by 235.3 and 67.26%. Built in twisted belt tube that was externally threaded was used by Sun *et al.* (2017) to study the flow characteristics and the heat transfer, the results showed that these tubes gave 50.32% rise in the coefficient of heat transfer if it was compared with horizontal tubes. Twisted tapes were studied numerically as well by Shaji (2016) which studied twisted tape inserted in a double pipe in this way they produced effect on the two sides of the pipe, the flow inside the pipe and the outlet heat exchanger annulus side. Some of the researchers studied the using of multi twisted tapes inside a single tube (Zhang *et al.*, 2012) numerically studied two insertions for the twisted tapes which were quadruple and triple. The results of the simulation indicated that the Nusselt number increased by 182% for the tube with twisted tapes quadruple inserted and 171% for the pipe

with twisted tapes triple inserted. The heat transfer was numerically investigated on a single, double and triple twisted tapes by Zhu and Chen (2015) with air flowing in the pipes, the heat transfer coefficient was improved by 1.8-4.5 times. Hong *et al.* (2017) performed an experiment using two wisted tape insert overlapped in a spiral grooved tube and plain tube. Air was used as the working fluid and different overlapped twisted ratio were tested 1.06, 1.56, 2.44 and 3.22 with Reynolds number ranging between 8000-22000. One of the methods used by Azmi *et al.* (2014) to rise the coefficient of heat transfer is to use new high performance conventional liquids with high thermal conductivity (TiO_2 /water nano fluid). They also used twisted tape inserted through the pipes. The heat transfer coefficient was boosted by 23.2% with 1% volume concentration of nano fluid but they originated that the coefficient of heat transfer decreased as the nano fluid concentration increased to 3% that if the heat transfer coefficient were compared with water flowing through the pipes. Maddah *et al.* (2014) used Al_2O_3 /water as the working fluid through a tube with twisted tape fitted inside using nano fluids lead to increase in the coefficient of heat transfer from 12-52%. Hamad and Jasim (2018) investigated experimentally the pressure drop and the coefficient of heat transfer of a condenser horizontal tube section for a two phase flow using refrigerant R-134a. the results of their experiments showed that the coefficient of heat transfer are highly effected by mass flux and heat flux. Kramallah *et al.* (2018) studied the nanofluid flow in an elliptical tube, the heat transfer coefficient found numerically using ANSYS Fluent. The results were compared with previous experimental tests, they found that the nusselt number increase with the increase in the nanoparticles volume

concentration. In this study, two methods to boost the heat transfer was applied which are using nanoparticles plus inserting a modified tape through the flow pipe. Normal structure for the TTI was studied as well as two modified ones with triangles shapes were added on the sides with different triangle angles.

MATERIALS AND METHODS

Model description: The geometry of the twisted tape inserted was generated using solidWorks 2013. Figure 1 shows both normal and modified structure of the TTI. The modification is performed by making triangles on the two sides of the tape. Two triangle dimensions were generated differencing in the triangle top angle, one with 90° and the other with 83°. The pipe for the TTI was generated using enclosure in ANSYS Fluent 15.0, Fig. 2 shows right view of the entire geometry. The pipe has length of 1000 mm and diameter of 50 mm. TTI has length of 994 mm, width of 16 mm and thickness of 1 mm. Twisting ratio was kept constant for all the models. Tetrahedrons mesh type was used which gave (85353, 86940 and 88511) elements and (17537, 18031 and 18391) nodes for the normal tape, the 90° tape and the 83° tape, respectively. Simulation was performed as horizontal pipe using fluent combined with ANSYS 15.0. Steady state with k-epsilon turbulent model was simulated. $\gamma\text{-Al}_2\text{O}_3/\text{water}$ was used as the flowing fluid, the nanoparticles properties are listed in Table 1. The diversity in choosing the velocities for the flowing fluid is considered, nine velocities was tested (0.15, 0.2, 0.25, 0.3, 0.6, 0.65, 0.9, 0.95 and 1.3 m/sec). Volume concentration for the nanoparticles used was 1%. Several equations were used to calculate the working fluid properties. The thermal conductivity calculated using Eq. 1 (Yu and Choi, 2004):

$$k_{nf} = k_{bf} \left[\frac{k_p + 2k_{bf} + 2(k_p - k_{bf})(1 + \beta)^3 \phi}{k_p + 2k_{bf} - (k_p - k_{bf})(1 + \beta)^3 \phi} \right] \quad (1)$$

Where, β is taken to be 0.1, Esmaeilzadeh *et al.* (2014) which is the ratio of nanolayer thickness to nanoparticle diameter. Equation 2 was used to calculate the nanofluid viscosity, Einstein (1956).

$$\mu_{nf} = (1 + 2.5\phi)\mu_{bf} \quad (2)$$

The density was calculated using Eq. 3, Pak and Cho (1998):

$$\rho_{nf} = (1 - \phi)\rho_{bf} + \phi\rho_p \quad (3)$$

The nanofluid specific heat was calculated using Eq. 4:

$$\rho_{nf}C_{p,nf} = (1 - \phi)\rho_{bf}C_{p,bf} + \phi\rho_pC_{p,p} \quad (4)$$

Fig. 1: Twisted tape geometry

Fig. 2: Right view for the geometry

Table 1: Properties of nanoparticles

Variables	Values
Density	3650 kg/m ³
Thermal conductivity	36 W/mK
Specific heat	733 j/kgk

RESULTS AND DISCUSSION

Model validation: The model was validated using the classical Eq. 5 of Dittus-Boelter (Lienhard and Lienhard, 2005):

$$Nu = 0.0243 Re^{0.8} Pr^n \quad (5)$$

For heating process $n = 0.4$. Figure 3 shows the comparison between the formula results and the fluent model calculations for a pipe with the same length and diameter without any tape inserted inside it. The maximum percentage of deviation between the two results was found to be 10% which can be considered good results.

Effect of tapes on Nusselt number: As the twisted tape was inserted into the pipe the nusselt number increased by 8.856 %, Fig. 4 shows the nusselt number with respect to Reynolds number for the pipe without twisted tape

Fig. 3: Comparison between Nu from the fluent model and the classical formula of Dittus-Boelter

Fig. 4: Nusselt number for pipe without TTI and with different types of TTI

inserted and with normal twisted tape. Figure 4 also shows the nusselt number for the two modified twisted tapes inserted, twisted tape with 90° triangle top angle gave 21.077% increase in the Nusselt number while twisted tape with 83° triangle top angle gave 48.22% increase in the nusselt number. Figure 4 shows that as the Reynolds number rise the nusselt number rise as well. Because of the helical passage of the flow and the pipe blockage that was created by the twisted tape the velocity of the flow will be higher at the pipe with twisted tapes more than the pipe without TTI (Hong *et al.*, 2017) which will give higher the nusselt number.

Fig. 5: The coefficient of heat transfer along the pipe with different velocities

Fig. 6: Comparison for the coefficient of heat transfer for the pipe without TTI and with modified TTI

Heat transfer coefficient along the pipe: The coefficient of heat transfer was calculated at different locations along the pipe. Figure 5 shows the coefficient of heat transfer against the distance x along the pipe with respect to two of the velocities were tested as shown in Fig. 5, for the modified structure TTI with 83° triangle top angle. The values of the coefficient of heat transfer seem to decrease at the medial of the pipe and have a high value at the start and end of the pipe. Figure 5 also shows that as the Reynolds number rise the Nusselt number rise as well. Figure 6 shows the coefficient of heat transfer with respect to the distance x along the pipe with and without a twisted tape inserted, in Fig. 6 the nanofluid inlet velocity is 0.15 m/sec. Figure 6 shows that the two pipes have the same effect for the heat transfer coefficient but with different values. Due to the twisted tape curvature the area of the heat transfer was bigger and the heat transfer was increase more that for the pipe without twisted tape inserted.

Fig. 7: Velocity vectors

Fig. 8: Temperature distributions

Velocity vectors and temperature distributions:

Figure 7 shows the velocity for the pipe with twisted tape inserted. Figure 7 shows high swirl created by the twisted tape due to the centrifugal force. The fluid mixing was also enhanced by the twisted tape. Figure 8 shows the contours of the temperature taken at plane at the middle of the pipe, the contours of the temperature shows that the temperature of the fluid at the tape curvature is higher.

CONCLUSION

The twisted was studied in this research numerically using ANSYS fluent 15.0. Both normal twisted tape and two modified structure were studied. Turbulent flow with several ranges of velocities were tested. The model was validated using formula developed by other research and the results were in good agreement. The conclusions drawn from this researchers are:

- Inserting tapes inside the pipes increase the heat transfer coefficient
- The modified tapes presented in this study (modified by adding triangles on the sides) increase the heat transfer coefficient
- The tapes with triangle of 83° angles have higher Nusselt number than that the ones with 90° angle

NOMENCLATURE

C_p	: Specific heat (J/kg.K)
d	: Width of the tape (m)
D	: Diameter of the pipe (m)
H	: Twisted tape pitch length (m)
h	: Heat transfer coefficient ($W/m^2.K$)
H/d	: Twist ratio
k	: Thermal conductivity (W/m.K)
Nu	: Nusselt number
Pr	: Prandtl number
Re	: Reynolds number
μ	: Viscosity (kg/msec)
ρ	: Density (kg/m^3)
ϕ	: Volume concentration
f	: Fluid (water)
p	: Particles (nano particles of $\gamma-Al_2O_3$)
TTI	: Twisted Tape Inserted

REFERENCES

- Azmi, W.H., K.V. Sharma, P.K. Sarma, R. Mamat and S. Anuar, 2014. Comparison of convective heat transfer coefficient and friction factor of TiO_2 nanofluid flow in a tube with twisted tape inserts. Intl. J. Therm. Sci., 81: 84-93.
- Einstein, A., 1956. Investigations on the Theory of Brownian Movement. Dover Publication Inc., New York, USA., ISBN:9780486603049, Pages: 119.
- Esmailzadeh, E., H. Almohammadi, A. Nokhosteen, A. Motezaker and A.N. Omrani, 2014. Study on heat transfer and friction factor characteristics of $\gamma-Al_2O_3$ /water through circular tube with twisted tape inserts with different thicknesses. Intl. J. Therm. Sci., 82: 72-83.

- Hamad, A.J. and R.A. Jasim, 2018. Experimental investigation of condensation heat transfer characteristics of R-134a vapor in horizontal heat exchanger. *J. Univ. Babylon Eng. Sci.*, 26: 16-31.
- Hong, Y., J. Du and S. Wang, 2017. Experimental heat transfer and flow characteristics in a spiral grooved tube with overlapped large/small twin twisted tapes. *Intl. J. Heat Mass Trans.*, 106: 1178-1190.
- Kramallah, A.A., N.S. Mahmoud and A.M. AL-Tajer, 2018. Numerical study of heat transfer and flow of nanofluid using multi-phase mixture model through elliptical tubes. *J. Univ. Babylon Eng. Sci.*, 26: 294-308.
- Lienhard, J.H. IV and J.H.V. Lienhard, 2005. *Heat Transfer Textbook*. 3rd Edn. Phlogiston Press, Cambridge MA.,.
- Maddah, H., M. Alizadeh, N. Ghasemi and S.R.W. Alwi, 2014. Experimental study of Al₂O₃/water nanofluid turbulent heat transfer enhancement in the horizontal double pipes fitted with modified twisted tapes. *Intl. J. Heat Mass Trans.*, 78: 1042-1054.
- Mokkapati, V. and C.S. Lin, 2014. Numerical study of an exhaust heat recovery system using corrugated tube heat exchanger with twisted tape inserts. *Intl. Commun. Heat Mass Trans.*, 57: 53-64.
- Pak, B.C. and Y.I. Cho, 1998. Hydrodynamic and heat transfer study of dispersed fluids with submicron metallic oxide particles. *Exp. Heat Trans. Intl. J.*, 11: 151-170.
- Shaji, K., 2016. Numerical analysis on a double pipe heat exchanger with twisted tape induced swirl flow on both sides. *Proc. Technol.*, 24: 436-443.
- Sun, B., A. Yang and D. Yang, 2017. Experimental study on the heat transfer and flow characteristics of nanofluids in the built-in twisted belt external thread tubes. *Intl. J. Heat Mass Trans.*, 107: 712-722.
- Yu, W. and S.U.S. Choi, 2004. The role of interfacial layers in the enhanced thermal conductivity of nanofluids: A renovated Hamilton-Crosser model. *J. Nanopart. Res.*, 6: 355-361.
- Zhang, X., Z. Liu and W. Liu, 2012. Numerical studies on heat transfer and flow characteristics for laminar flow in a tube with multiple regularly spaced twisted tapes. *Intl. J. Therm. Sci.*, 58: 157-167.
- Zhu, J.D. and H. Chen, 2015. Numerical study on enhanced heat transfer by twisted tape inserts inside tubes. *Proc. Eng.*, 130: 256-262.