Calibration of Industrial Robot Kinematics Based on Results of Interpolating Error by Shape Function

Thuy Le Thi Thu, Khanh Duong Quoc and Long Pham Thanh
Division of Mechatronics, Faculty of Mechanical Engineering,
Thai Nguyen University of Technology, Street No. 666, 3/2, Tich Luong Ward,
Thai Nguyen City, Thai Nguyen Province, Vietnam

Abstract: The initial accuracy of a robot arm depends not only on the hardware's manufacturing and assembly quality but also on control strategies. During assembly or regular maintenance, the kinematic accuracy of a robot arm needs to be verified and calibrated to maintain the desired quality. In this study, we present a method to determine and correct the robot kinematic error based on the shape function interpolation technique. Experimental research was applied to aABB robot with six degrees of freedom to verify the correctness of the method. The results indicated that the position errors of the end-effector were significantly reduced. The effectiveness of the proposed interpolation method and combined error compensation algorithm demonstrated that practical application is feasible.

Key words: Calibration, error kinematics, interpolation, shape function, industrial robot, application

INTRODUCTION

Today, robotic arms play an important role in industrial applications. The accuracy of these manipulators should be maintained over time to ensure product quality. As such, many studies have been conducted to improve the calibration and maintain the desired accuracy of robot grippers. These studies are classified into two methods: model-based and modelless. The classical model-based method for robot calibration involves setting up a kinematic model for the robot, measuring positions and orientations of the robot end-effector, identifying its kinematic parameters and compensating its pose errors by modifying its joint angles (Mooring *et al.*, 1991). The advantage of model-based calibration is that a large workspace can be calibrated accurately and all pose errors within the calibrated workspace can be compensated by joint angles (Bai and Wang, 2006). Therefore, a significant amount of research has been performed in this direction. Several recently published studies-such as that by Wang *et al.* (2012) used genetic algorithms to build mathematically calibrated equations to compensate the kinematic errors cylindrical-coordinate-based manipulator with three Degrees of Freedom (DOF). Ma *et al.* (2018) conducted modelling and calibration of high-order joint-dependent kinematic errors for industrial robots. The process was performed using high-order Chebyshev polynomials to represent individual error terms and a laser tracker system to acquire the measured data. Laser tracker systems are often used in studies of kinematic error calibration of

series and parallel robots (Abderrahim *et al.*, 2006; Kamali *et al.*, 2016; Sun *et al.*, 2016). Yu and Xi (2018) presented a self-calibration method based on measuring the centers of four spherical calibration targets located around the inspecting system. Their global kinematic model was developed based on a Modified Denavit-Hartenberg (MDH) Model without separating the hand-eye and robot exterior models. The MDH method and Hayati convention were also used by Kong *et al.* (2018) to calibrate the kinematics and enhance the accuracy of a 3-PRRU parallel manipulator through the effect of error of its universal joints. However, the disadvantage of the model-based method is that an understanding of modelling and identification processes requires advanced knowledge of robot kinematics.

In the modelless method, kinematic modelling and identification steps are not required. The disadvantage is that the accuracy depends on the number of grid points. However because of its simplicity and efficiency, the modelless technique is widely applied in industrial fields. Several researchers have conducted error calibration of robotic arms through this interpolation technique. Liu *et al.* (2018) proposed a trajectory planning technique to minimise the synthetic error of the end-effectors of industrial robots. Kinematic and dynamic models were built using screw theory and Kane equations and subsequently, the end-effector synthesis error was modelled by considering the effect of interpolated algorithms and the flexibility of all joints. The septic polynomial was used to interpolate the via. points in joint space and the PSO algorithm was applied to find the

minimum synthesis error. In Bai and Wang (2016), used an Interval Type-2 Fuzzy Error Interpolation method (IT2FEI) to compensate the calibration accuracy of a robot in a 3D workspace. Theirs was compared to other nominal interpolation methods: type-1 fuzzy, trilinear and cubic spline. Meanwhile, Borrmann and Wollnack (2014) used a laser tracker to measure the position and direction of the linear axis. B-spline interpolation was used to model the external axis which allowed for prediction of the linear axis pose. Bai and Wang (2006, 2003a, b, 2004), Bai and Zhuang (2004, 2005), Bai *et al.* (2008), presented a modelless technique in combination with an online fuzzy interpolation method to calibrate the accuracy of a serial and parallel (Stewart Platform) robot.

MATERIALS AND METHODS

In this study, the researchers present a procedure for determining errors according to the modelless method with shape function interpolation techniques. Calibration is then performed to minimise the kinematic errors of the end-effector of a robot. The general process is described in Fig. 1.

RESULTS AND DISCUSSION

The rest of this study is organized as follows: first, the determination of a robot's end-effector error is presented as two primary steps: measure the errors at certain poses in the survey space by an experimental measuring system and from those sample poses, establish the shape function interpolation to compute the errors of the entire survey area. The second section, errors. In the third section, the effectiveness of the proposed method is verified on a ABB robot with six DOF (6DOF). The final section outlines the conclusions.

Determining kinematic errors of robot end-effector
Basis of determining end-effector errors of robot at sample poses in the workspace: To predict the errors of the robot end-effector in the workspace, several sample poses need to be measured experimentally to find the actual errors. These errors are used as input to construct interpolation functions for predicting the deviations of the gripper at other poses in the survey space.

Manipulators always face objective obstacles such as link parameter errors, clearances in the mechanism's

connections, wear, thermal effects, flexibility of the links and gear train, gear backlash, encoder resolution errors, errors associated with relating the theoretical robot coordinate frame to the world coordinate frame and control errors (Hayati *et al.*, 1988). Therefore, when controlled to reach the desired pose $P(P_x, P_y, P_z)$, the tip of the robot will reach the pose with the real coordinate $P'(p_x \pm \delta_x, p_y \pm \delta_y, p_z \pm \delta_z)$ in which at various poses throughout the workspace and even at the same pose, the errors $(\delta_x, \delta_y, \delta_z)$ are different. The manufacturer's published value for these errors is statistically significant. The errors will increase with the service time of the robot. In performing the study, we used a robot with a software interface designed to be able to read both the coordinates of pose $P(P_x, P_y, P_z)$ and the corresponding generalized coordinates $P(q_1, \dots, q_n)$.

In Fig. 2, the coordinate origin O_0 of the robot is determined as the center of the top face of a cylindrical cotter pin located in the robot body. When the cylindrical pin is placed in the base of the manipulator, its center is on the first axis of rotation. Therefore, in the kinematic model, the robot arm is at coordinate origin O_0 .

The purpose of setting this pin is to transfer the virtual origin O_0 into a real one, thereby allowing the camera see and determine its location. Subsequently, the camera software determines the conversion of the coordinate system to convert all observed data through this origin point O_0 of the robot.

The two pins are set in a high-precision jig at a distance of d from one another, as shown in Fig. 3. The position and direction relations between them are determined by the transfer matrix:

$$O_0 * A_{O_0}^{O_c} \rightarrow O_c \quad (1)$$

Where, O_c is the origin of the reference system attached to the camera.

At this time, there are two independent observation channels:

- Coordinate $P(P_x, P_y, P_z)$ is the desired pose. It is determined based on the encoders $e_1, e_2, \dots, e_n$ as shown in Fig. 3 and displayed on the interface of the robot
- Real coordinate $P'(p_x \pm \delta_x, p_y \pm \delta_y, p_z \pm \delta_z)$ is that determined independently by the camera and transferred to an origin O_0 relation according to Eq. 1

Fig. 1: Outline of the proposed method

Fig. 2: Position of basic reference coordinate system on cylindrical cotter pin and position of the pin in the manipulator

Fig. 3: Camera and robot arranged on a specific jig to identify the origin point O_0

Comparing these two coordinates will produce the absolute error of the robot end-effector in pose P ($\delta_x, \delta_y, \delta_z$).

Error prediction with shape function: Data obtained by direct measurement of the entire workspace have a high time cost and are not suitable for industrial production conditions. As such, we replaced the measured data with interpolated data before error compensation. Accordingly, the error calibration process was accelerated.

In the workspace, a group of sample points are used to form the survey space. These points are referred to as nodes and are associated with other individual points. Once the errors corresponding to each node have been determined through direct measurement, errors at arbitrary positions in the survey space can be interpolated by introducing a suitable interpolation scheme. For this, three-dimensional interpolation is implemented with shape functions.

If there are n nodes, n shape functions will be defined. With the determination of the end-effector error of the robot consisting of six components

Fig. 4: Influence of sampling points on a survey point through shape function

(three orientation and three position components), to compute the coefficients of the shape functions, the survey space is selected to include six nodes. In this case, the researchers selected the survey space as a triangular prism; i.e., six sampled points will form a six-node brick element.

Suppose the error at survey pose P_i consists of six components as follows:

$$\delta P_i = (\delta_x^i, \delta_y^i, \delta_z^i, \delta_{\theta x}^i, \delta_{\theta y}^i, \delta_{\theta z}^i) \quad (2)$$

Consider the survey space as shown in Fig. 4. In this field, the errors are measured at the vertices of the prism with each vertex corresponding to the six components in Eq. 2.

At pose P_i in the triangular prism, the following relationships are established:

$$\left\{ \begin{array}{l} \delta_x^{(i)} = N_A \cdot \delta_x^{(A)} + N_B \cdot \delta_x^{(B)} + \dots + N_F \cdot \delta_x^{(F)} \\ \dots \\ \delta_{\theta z}^{(i)} = N_A \cdot \delta_{\theta z}^{(A)} + N_B \cdot \delta_{\theta z}^{(B)} + \dots + N_F \cdot \delta_{\theta z}^{(F)} \end{array} \right\} \quad (3)$$

Where, $\delta_x^{(i)}, \delta_y^{(i)}, \delta_z^{(i)}, \delta_{\theta x}^{(i)}, \delta_{\theta y}^{(i)}, \delta_{\theta z}^{(i)}$ are the six component errors at pose P_i .

N_A, N_B, N_C, N_D, N_E and N_F are the stationary coefficients of the shape functions that affect the error at pose P_i from the six corresponding nodes and are the $\delta_x^{(A)}, \delta_y^{(A)}, \delta_z^{(A)}, \delta_{\theta x}^{(A)}, \delta_{\theta y}^{(A)}, \delta_{\theta z}^{(A)}, \delta_x^{(F)}, \delta_y^{(F)}, \delta_z^{(F)}, \delta_{\theta x}^{(F)}, \delta_{\theta y}^{(F)}, \delta_{\theta z}^{(F)}$ are the actual component error values for position and direction (directly measured) of the six corresponding A...F vertices.

From Eq. 3, the stationary coefficients of the shape function can then be found by:

$$\begin{bmatrix} N_A \\ \dots \\ N_F \end{bmatrix}_{(i)} = \begin{bmatrix} \delta_x^{(A)} & \dots & \delta_x^{(F)} \\ \dots & \dots & \dots \\ \delta_{\theta_z}^{(A)} & \dots & \delta_{\theta_z}^{(F)} \end{bmatrix}^{-1} \begin{bmatrix} \delta_x^{(i)} \\ \dots \\ \delta_{\theta_z}^{(i)} \end{bmatrix} \quad (4)$$

where in the right-hand side of the equation, the square matrix is the measured error values of the vertices A, ..., F and the matrix $\begin{bmatrix} \delta_x^{(i)} & \dots & \delta_{\theta_z}^{(i)} \end{bmatrix}$ is the measured error values at the survey pose P_i in the prism, $[N_A, \dots, N_F]_{(i)}^T$ is the stationary values of six shape functions impacting the errors at pose P_i .

After n survey poses, the result is a set of n sets of stationary values of six shape functions, as follows:

$$\begin{bmatrix} N_A \\ \dots \\ N_F \end{bmatrix}_{(1)} ; \dots ; \begin{bmatrix} N_A \\ \dots \\ N_F \end{bmatrix}_{(i)} ; \dots ; \begin{bmatrix} N_A \\ \dots \\ N_F \end{bmatrix}_{(n)} \quad (5)$$

Thus, the regression law allows for the determination of the experimental shape function at vertex k as follows:

$$(N_k^{(1)}, \dots, N_k^{(i)}, \dots, N_k^{(n)}) \Rightarrow f_k(x, y, z) \quad (k = A, B, C, D, E, F) \quad (6)$$

At this time, according to Eq. 3, it is possible to calculate explicitly the error at pose P_i having arbitrary coordinates in the survey prism. Subsequently, the interpolated errors at this pose are determined by the shape functions. This procedure greatly reduces the complexity and computational burden associated with direct evaluation of the errors and as will be demonstrated can result in remarkable prediction accuracy (Wang *et al.*, 2002).

Compensation of end-effector error based on results interpolation: As kinematic error is the primary source of inaccuracy in a robot end-effector Weill and Shani (1991) Conrad *et al.* (2000), it must be sufficiently compensated. The basis of the proposed error compensation method is to control the robot to an alternate pose instead of the desired pose.

The basis of the error compensation method herein is to control the robot to an alternate pose instead of the desired pose. This alternative point is proposed to compensate for kinematic errors that appear when the robot gripper is controlled straight to the desired destination.

Let:

$$P_i(x_i, y_i, z_i, \theta_x^{(i)}, \theta_y^{(i)}, \theta_z^{(i)})$$

and

$$P_i^t \left(x_i \pm \delta_x^{(i)}, y_i \pm \delta_y^{(i)}, z_i \pm \delta_z^{(i)}, \theta_x^{(i)} \pm \delta_{\theta_x}^{(i)}, \theta_y^{(i)} \pm \delta_{\theta_y}^{(i)}, \theta_z^{(i)} \pm \delta_{\theta_z}^{(i)} \right)$$

Be the desired coordinate of the manipulator and the actual coordinate recorded by interpolation using the shape function, respectively for the same survey pose (P_i) (Fig. 5). Thus, there exists a deviation of six components between them:

$$\delta P_i = (\pm \delta_x^i, \pm \delta_y^i, \pm \delta_z^i, \pm \delta_{\theta_x}^i, \pm \delta_{\theta_y}^i, \pm \delta_{\theta_z}^i)$$

To reduce this error, we propose to replace pose P_i when solving the inverse kinematic problem with pose P_i^t , which is determined from the desired coordinate and its errors as follows:

$$P_i^t \left(x_i \pm \delta_x^{(i)}, y_i \pm \delta_y^{(i)}, z_i \pm \delta_z^{(i)}, \theta_x^{(i)} \pm \delta_{\theta_x}^{(i)}, \theta_y^{(i)} \pm \delta_{\theta_y}^{(i)}, \theta_z^{(i)} \pm \delta_{\theta_z}^{(i)} \right) \quad (7)$$

After resolving the inverse kinematic problem with the destination as P_i^t instead of P_i , the result will be significantly improved accuracy (Table 1).

Illustrative examples and experimental results: In this section, an experimental survey is presented to verify the proposed theories. The system consists of a 6DOF ABB robot and Cognex 3D-A5005 area scan 3D camera. The kinematic parameters of the robot are shown in Table 2. The camera has an XY resolution of 44 μ m, Z resolution of 8 μ m and repeatability of 6 μ m. In this experiment, the camera was calibrated with a Root Mean Square (RMS) index of 0.005 mm (Fig. 6).

Table 1: D-H link parameter table

Joint i	R_z	T_z	T_x	R_x
1	(α_1)	d_1	a_1	90°
2	(α_2)	0	a_2	0
3	(α_3)	0	a_3	90°
4	(α_4)	d_4	0	-90°
5	(α_5)	0	0	90°
6	(α_6)	d_5+d_6	0	0

Table 2: Nominal link lengths (mm)

d_1	a_1	a_2	a_3	d_4	d_5+d_6
335	75	270	90	295	80

Fig. 5: Kinematic modelling of ABB

Fig. 6: Experimental diagram

Error interpolation by shape function: Assuming the robot's operational space in the experiment is a rectangular prism (as shown in Fig. 7), construction of the shape function is performed in each constituent triangular prism-ABCDEF and AGCDHF to predict the end-effector errors.

Interpolation of errors in prism 1-ABCDEF: The survey space is a triangular prism with vertices of six nodes: A, B, C, D, E and F. The experimental process was conducted with 54 grid points in this space. Two data points describing the pose at these points are recorded independently: the nominal pose displayed on the robot controller and the actual one

Fig. 7: Survey prism for predicting end-effector errors

recorded by the 3D camera. These values are then compared to acquire the errors at point P_i .

Table 3 shows the nominal and real position values and errors. In the table, a_{13} , a_{23} and a_{12} represent 3 values about the orientation $\cos(x_0, z_6)$, $\cos(y_0, z_6)$ and $\cos(x_0, y_6)$ and a_{14} , a_{24} and a_{34} are the positions p_x , p_y and p_z , respectively.

The set of error values of the six nodes and 54 grid points is used as input to construct the shape functions for predicting the end-effector errors as described in section 2.2. The shape functions in the survey space are determined by an experimental regression in Minitab Software, as follows:

$$N_A = -18.48 + 0.0675 * X + 0.0318 * Y + 0.0219 * Z + 0.000005 * X * X + 0.000090 * Y * Y + 0.000049 * Z * Z - 0.000145 * X * Y - 0.000100 * X * Z - 0.000094 * Y * Z$$

$$N_B = 10.08 - 0.0307 * X - 0.0123 * Y - 0.0157 * Z + 0.000016 * X * X - 0.000091 * Y * Y - 0.000021 * Z * Z + 0.000081 * X * Y - 0.000000 * X * Z + 0.000095 * Y * Z$$

$$N_C = 12.59 - 0.0404 * X - 0.0178 * Y - 0.0211 * Z - 0.000025 * X * X - 0.000015 * Y * Y - 0.000017 * Z * Z + 0.000083 * X * Y + 0.000099 * X * Z - 0.000002 * Y * Z$$

$$N_D = 13.64 - 0.0526 * X - 0.0258 * Y - 0.0287 * Z + 0.000009 * X * X - 0.000053 * Y * Y - 0.000037 * Z * Z + 0.000101 * X * Y + 0.000101 * X * Z + 0.000097 * Y * Z$$

$$N_E = -7.76 + 0.0332 * X - 0.0000 * Y + 0.0211 * Z - 0.000030 * X * X + 0.000085 * Y * Y + 0.000011 * Z * Z - 0.000065 * X * Y - 0.000000 * X * Z - 0.000096 * Y * Z$$

$$N_F = -8.94 + 0.0218 * X + 0.0240 * Y + 0.0234 * Z + 0.000024 * X * X - 0.000020 * Y * Y + 0.000014 * Z * Z - 0.000050 * X * Y - 0.000100 * Y * Z - 0.000000 * Y * Z$$

Table 3: Nominal and real pose values at survey points

Point	Desired position			Measured pose						Measured pose errors					
	X	Y	Z	a_{13}	a_{23}	a_{12}	a_{14}	a_{24}	a_{34}	δa_{13}	δa_{23}	δa_{12}	δa_{14}	δa_{24}	δa_{34}
A	300	275	200	-0.001	0.000	-0.743	299.415	274.955	200.357	-0.001	0.000	0.000	-0.585	-0.045	0.357
B	300	175	200	-0.001	0.000	-0.743	299.604	175.132	200.408	-0.001	0.000	0.000	-0.396	0.132	0.408
C	200	275	200	-0.001	-0.001	-0.743	199.602	274.975	200.413	-0.001	-0.001	0.000	-0.398	-0.025	0.413
D	300	275	300	-0.001	0.000	-0.743	299.555	275.075	300.257	-0.001	0.000	0.001	-0.445	0.075	0.257
E	300	175	300	-0.001	0.000	-0.743	299.778	175.223	300.356	-0.001	0.000	0.001	-0.222	0.223	0.356
F	200	275	300	-0.001	-0.001	-0.743	199.725	275.130	300.368	-0.001	-0.001	0.001	-0.275	0.130	0.368
P1	240	255	210	-0.001	0.000	-0.743	239.592	255.026	210.398	-0.001	0.000	0.000	-0.408	0.026	0.398
P2	260	255	210	-0.001	0.000	-0.743	259.555	255.020	210.387	-0.001	0.000	0.000	-0.445	0.020	0.387
P3	280	255	210	-0.001	0.000	-0.743	279.514	255.015	210.374	-0.001	0.000	0.000	-0.486	0.015	0.374
P4	260	235	210	-0.001	0.000	-0.743	259.595	235.058	210.398	-0.001	0.000	0.000	-0.405	0.058	0.398
P5	280	235	210	-0.001	0.000	-0.743	279.554	235.053	210.385	-0.001	0.000	0.000	-0.446	0.053	0.385
P6	280	215	210	-0.001	0.000	-0.743	279.593	215.087	210.396	-0.001	0.000	0.000	-0.407	0.087	0.396
P7	240	255	220	-0.001	0.000	-0.743	239.608	255.042	220.392	-0.001	0.000	0.001	-0.392	0.042	0.392
P8	260	255	220	-0.001	0.000	-0.743	259.571	255.035	220.379	-0.001	0.000	0.000	-0.429	0.035	0.379
P9	280	255	220	-0.001	0.000	-0.743	279.531	255.029	220.365	-0.001	0.000	0.000	-0.469	0.029	0.365
P10	260	235	220	-0.001	0.000	-0.743	259.612	235.073	220.391	-0.001	0.000	0.001	-0.388	0.073	0.391
P11	280	235	220	-0.001	0.000	-0.743	279.571	235.067	220.377	-0.001	0.000	0.000	-0.429	0.067	0.377
P12	280	215	220	-0.001	0.000	-0.743	279.611	215.101	220.389	-0.001	0.000	0.001	-0.389	0.101	0.389
P13	240	255	230	-0.001	0.000	-0.743	239.624	255.057	230.385	-0.001	0.000	0.001	-0.376	0.057	0.385
P14	260	255	230	-0.001	0.000	-0.743	259.587	255.050	230.371	-0.001	0.000	0.001	-0.413	0.050	0.371
P15	280	255	230	-0.001	0.000	-0.743	279.547	255.043	230.356	-0.001	0.000	0.001	-0.453	0.043	0.356
P16	260	235	230	-0.001	0.000	-0.743	259.629	235.087	230.385	-0.001	0.000	0.001	-0.371	0.087	0.385
P17	280	235	230	-0.001	0.000	-0.743	279.588	235.080	230.370	-0.001	0.000	0.001	-0.412	0.080	0.370
P18	280	215	230	-0.001	0.000	-0.743	279.629	215.113	230.383	-0.001	0.000	0.001	-0.371	0.113	0.383
P19	240	255	240	-0.001	0.000	-0.743	239.639	255.072	240.380	-0.001	0.000	0.001	-0.361	0.072	0.380
P20	260	255	240	-0.001	0.000	-0.743	259.602	255.064	240.365	-0.001	0.000	0.001	-0.398	0.064	0.365
P21	280	255	240	-0.001	0.000	-0.743	279.562	255.056	240.348	-0.001	0.000	0.001	-0.438	0.056	0.348
P22	260	235	240	-0.001	0.000	-0.743	259.645	235.101	240.379	-0.001	0.000	0.001	-0.355	0.101	0.379
P23	280	235	240	-0.001	0.000	-0.743	279.604	235.092	240.363	-0.001	0.000	0.001	-0.396	0.092	0.363
P24	280	215	240	-0.001	0.000	-0.743	279.646	215.126	240.377	-0.001	0.000	0.001	-0.354	0.126	0.377
P25	240	255	250	-0.001	0.000	-0.743	239.653	255.086	250.375	-0.001	0.000	0.001	-0.347	0.086	0.375
P26	260	255	250	-0.001	0.000	-0.743	259.617	255.077	250.358	-0.001	0.000	0.001	-0.383	0.077	0.358
P27	280	255	250	-0.001	0.000	-0.743	279.577	255.068	250.340	-0.001	0.000	0.001	-0.423	0.068	0.340
P28	260	235	250	-0.001	0.000	-0.743	259.660	235.114	250.374	-0.001	0.000	0.001	-0.340	0.114	0.374
P29	280	235	250	-0.001	0.000	-0.743	279.620	235.105	250.356	-0.001	0.000	0.001	-0.380	0.105	0.356
P30	280	215	250	-0.001	0.000	-0.743	279.663	215.137	250.371	-0.001	0.000	0.001	-0.337	0.137	0.371
P31	240	255	260	-0.001	0.000	-0.743	239.667	255.100	260.370	-0.001	0.000	0.001	-0.333	0.100	0.370
P32	260	255	260	-0.001	0.000	-0.743	259.631	255.090	260.352	-0.001	0.000	0.001	-0.369	0.090	0.352
P33	280	255	260	-0.001	0.000	-0.743	279.591	255.080	260.333	-0.001	0.000	0.001	-0.409	0.080	0.333
P34	260	235	260	-0.001	0.000	-0.743	259.675	235.126	260.369	-0.001	0.000	0.001	-0.325	0.126	0.369
P35	280	235	260	-0.001	0.000	-0.743	279.635	235.116	260.350	-0.001	0.000	0.001	-0.365	0.116	0.350
P36	280	215	260	-0.001	0.000	-0.743	279.678	215.148	260.366	-0.001	0.000	0.001	-0.322	0.148	0.366
P37	240	255	270	-0.001	0.000	-0.743	239.680	255.112	270.365	-0.001	0.000	0.001	-0.320	0.112	0.365
P38	260	255	270	-0.001	0.000	-0.743	259.644	255.102	270.346	-0.001	0.000	0.001	-0.356	0.102	0.346
P39	280	255	270	-0.001	0.000	-0.743	279.605	255.092	270.326	-0.001	0.000	0.001	-0.395	0.092	0.326
P40	260	235	270	-0.001	0.000	-0.743	259.689	235.137	270.364	-0.001	0.000	0.001	-0.311	0.137	0.364
P41	280	235	270	-0.001	0.000	-0.743	279.649	235.127	270.344	-0.001	0.000	0.001	-0.351	0.127	0.344
P42	280	215	270	-0.001	0.000	-0.743	279.693	215.158	270.361	-0.001	0.000	0.001	-0.307	0.158	0.361
P43	240	255	280	-0.001	0.000	-0.743	239.692	255.124	280.360	-0.001	0.000	0.001	-0.308	0.124	0.360
P44	260	255	280	-0.001	0.000	-0.743	259.657	255.113	280.340	-0.001	0.000	0.001	-0.343	0.113	0.340
P45	280	255	280	-0.001	0.000	-0.743	279.618	255.102	280.318	-0.001	0.000	0.001	-0.382	0.102	0.318
P46	260	235	280	-0.001	0.000	-0.743	259.703	235.148	280.360	-0.001	0.000	0.001	-0.297	0.148	0.360
P47	280	235	280	-0.001	0.000	-0.743	279.663	235.137	280.338	-0.001	0.000	0.001	-0.337	0.137	0.338
P48	280	215	280	-0.001	0.000	-0.743	279.708	215.168	280.356	-0.001	0.000	0.001	-0.292	0.168	0.356
P49	240	255	290	-0.001	0.000	-0.743	239.704	255.135	290.356	-0.001	0.000	0.001	-0.296	0.135	0.356
P50	260	255	290	-0.001	0.000	-0.743	259.669	255.124	290.334	-0.001	0.000	0.001	-0.331	0.124	0.334
P51	280	255	290	-0.001	0.000	-0.743	279.630	255.113	290.311	-0.001	0.000	0.001	-0.370	0.113	0.311
P52	260	235	290	-0.001	0.000	-0.743	259.715	235.158	290.355	-0.001	0.000	0.001	-0.285	0.158	0.355
P53	280	235	290	-0.001	0.000	-0.743	279.675	235.147	290.332	-0.001	0.000	0.001	-0.325	0.147	0.332
P54	280	215	290	-0.001	0.000	-0.743	279.721	215.177	290.351	-0.001	0.000	0.001	-0.279	0.177	0.351

Where, N_A , N_B , N_C , N_D , N_E and N_F are the shape functions describing the error influence from nodes A, B, C, D, E and F, respectively on point Pi with coordinates (X, Y, Z).

Interpolation of errors in prism 2-AGCDHF: The same process is followed for the second prism to produce the following regression:

$$N_A = 118.1 + 0.649*X + 0.285*Y - 1.873*Z \\ - 0.001090*X*X - 0.000363*Y*Y + 0.003799*Z*Z \\ - 0.000605*X*Y + 0.000004*X*Z - 0.000010*Y*Z$$

$$N_G = -67.8 - 0.401*X - 0.172*Y + 1.1179*Z \\ + 0.000692*X*X + 0.000165*Y*Y - 0.002284*Z*Z \\ + 0.000392*X*Y - 0.000044*X*Z + 0.000067*Y*Z$$

$$N_C = -55.1 - 0.311*X - 0.144*Y + 0.8996*Z \\ + 0.000492*X*X + 0.000223*Y*Y - 0.001836*Z*Z \\ + 0.000294*X*Y + 0.000047*X*Z - 0.000048*Y*Z$$

$$N_D = -111.7 - 0.646*X - 0.280*Y + 1.830*Z \\ + 0.001055*X*X + 0.000317*Y*Y - 0.003708*Z*Z \\ + 0.000636*X*Y - 0.000007*X*Z + 0.000007*Y*Z$$

$$N_H = 67.6 + 0.434*X + 0.167*Y - 1.1496*Z \\ - 0.000725*X*X - 0.000139*Y*Y + 0.002350*Z*Z \\ - 0.000428*X*Y + 0.000042*X*Z - 0.000069*Y*Z$$

$$N_F = 49.4 + 0.2696*X + 0.1407*Y - 0.8120*Z \\ - 0.000417*X*X - 0.000204*Y*Y + 0.001653*Z*Z \\ - 0.000280*X*Y - 0.000043*X*Z + 0.000053*Y*Z$$

This result is used to predict the end-effector error at any position in the survey space. Because the interpolation is based on directly measured errors, it

includes all component error sources. Hence, the interpolated error values are implicitly the synthesis errors.

Verification survey: To verify whether the shape function has been met, we compared the errors at 10 random points in the survey space. Errors were taken from two separate sources: those directly measured and those predicted from shape functions. The deviations are shown in Table 4.

The graph in Fig. 8 shows the correlation between the position deviation of the end-effector measured experimentally and that determined by the shape function in the X, Y and Z directions. In the graphs, the red line represents the error measured experimentally and the blue represents the error interpolated from the shape function.

The charts show that the robot end-effector error interpolated from the shape function has a deviation from the experimental measurement in the range from 0-0.035 mm. Thus, the interpolation result can be used to replace the direct measurement results. This saves considerable time and cost for designing, calibrating and determining robot error.

Compensation of end-effector error based on interpolation results: Using the compensatory solutions proposed in section 3, the research team conducted a survey at 15 random poses in the prism. The calculation position for compensation was taken from a comparison between two values: the position after being predicted by the shape function and the nominal one. The inverse kinematic problem is then solved to acquire the set of joint variables for the actual control process. Data collected with the ABB robot before and after compensation is summarized in Table 5.

Table 4: Verifying end-effector errors at certain poses

	Nominal coordinates			End-effector errors from direct measurements						End-effector errors from interpolating shape function					
Pose	X	Y	Z	δa_{13}	δa_{23}	δa_{17}	δa_{14}	δa_{24}	δa_{34}	δa_{13}	δa_{23}	δa_{17}	δa_{14}	δa_{24}	δa_{34}
P55	250	255	215	-0.001	0.000	0.000	-0.418	0.031	0.389	-0.001	0.000	0.000	-0.399	0.023	0.357
P56	260	255	215	-0.001	0.000	0.000	-0.437	0.028	0.383	-0.001	0.000	0.000	-0.416	0.021	0.349
P57	280	245	218	-0.001	0.000	0.000	-0.452	0.046	0.373	-0.001	0.000	0.000	-0.429	0.039	0.338
P58	260	235	218	-0.001	0.000	0.001	-0.392	0.070	0.393	-0.001	0.000	0.000	-0.371	0.065	0.363
P59	280	235	223	-0.001	0.000	0.001	-0.424	0.071	0.375	-0.001	0.000	0.000	-0.402	0.066	0.343
P60	270	215	223	-0.001	0.000	0.001	-0.362	0.108	0.394	-0.001	0.000	0.000	-0.342	0.106	0.366
P61	240	255	234	-0.001	0.000	0.001	-0.370	0.063	0.383	-0.001	0.000	0.000	-0.354	0.056	0.354
P62	260	253	234	-0.001	0.000	0.001	-0.403	0.059	0.370	-0.001	0.000	0.000	-0.384	0.053	0.339
P63	272	255	246	-0.001	0.000	0.001	-0.413	0.067	0.350	-0.001	0.000	0.000	-0.393	0.061	0.318
P64	260	240	246	-0.001	0.000	0.001	-0.357	0.100	0.372	-0.001	0.000	0.001	-0.340	0.095	0.344
P65	280	235	248	-0.001	0.000	0.001	-0.383	0.102	0.358	-0.001	0.000	0.000	-0.364	0.099	0.327
P66	282	215	248	-0.001	0.000	0.001	-0.345	0.134	0.370	-0.001	0.000	0.001	-0.327	0.133	0.342
P67	240	249	252	-0.001	0.000	0.001	-0.331	0.100	0.379	-0.001	0.000	0.001	-0.318	0.094	0.352
P68	265	255	252	-0.001	0.000	0.001	-0.390	0.077	0.352	-0.001	0.000	0.001	-0.373	0.072	0.321
P69	280	240	265	-0.001	0.000	0.001	-0.369	0.113	0.343	-0.001	0.000	0.001	-0.352	0.110	0.312
P70	270	235	265	-0.001	0.000	0.001	-0.337	0.126	0.357	-0.001	0.000	0.001	-0.322	0.124	0.328
P71	280	235	277	-0.001	0.000	0.001	-0.341	0.134	0.340	-0.001	0.000	0.001	-0.326	0.132	0.311
P72	274	215	277	-0.001	0.000	0.001	-0.284	0.168	0.364	-0.001	0.000	0.001	-0.271	0.169	0.338
P73	240	245	288	-0.001	0.000	0.001	-0.275	0.151	0.368	-0.001	0.000	0.001	-0.267	0.147	0.343
P74	257	253	288	-0.001	0.000	0.001	-0.323	0.127	0.340	-0.001	0.000	0.001	-0.313	0.123	0.314

Table 5: Robot end-effector errors before and after compensation at random survey poses

Nominal coordinates				Error after compensation													
				Initial error							Average position error (spherical radius)						
Pose	X	Y	Z	δa_{13}	δa_{23}	δa_{12}	δa_{14}	δa_{24}	δa_{34}	Average position error (spherical radius)	δa_{13}	δa_{23}	δa_{12}	δa_{14}	δa_{24}	δa_{34}	Average position error (spherical radius)
P1	220	195	210	0.001	0.000	-0.001	-0.437	-0.126	-0.761	0.886	-0.001	-0.001	0.001	0.118	-0.157	0.207	0.285
P11	240	215	220	0.001	0.000	-0.001	-0.470	-0.129	-0.790	0.928	-0.001	-0.001	0.001	0.125	-0.180	0.217	0.309
P17	240	215	230	0.001	0.000	-0.001	-0.449	-0.110	-0.810	0.933	-0.001	-0.001	0.001	0.119	-0.186	0.216	0.309
P23	240	215	240	0.001	0.000	-0.001	-0.428	-0.091	-0.829	0.937	-0.001	-0.001	0.001	0.113	-0.191	0.215	0.309
P32	240	195	260	0.001	0.000	-0.001	-0.359	-0.025	-0.861	0.934	-0.001	-0.001	0.001	0.085	-0.198	0.207	0.299
P38	240	195	270	0.001	0.000	-0.001	-0.337	-0.006	-0.877	0.940	-0.001	-0.001	0.001	0.079	-0.203	0.206	0.300
P44	240	195	280	0.001	0.000	-0.001	-0.314	0.013	-0.892	0.946	-0.001	-0.001	0.001	0.073	-0.209	0.204	0.301
P49	220	195	290	0.001	0.000	-0.001	-0.260	0.031	-0.904	0.941	-0.001	-0.001	0.001	0.068	-0.201	0.196	0.289
P53	240	215	290	0.001	0.000	-0.001	-0.322	0.005	-0.909	0.965	-0.001	-0.001	0.001	0.083	-0.219	0.206	0.312
P27	260	195	250	0.001	0.000	-0.001	-0.418	-0.038	-0.848	0.946	-0.001	-0.001	0.001	0.090	-0.207	0.215	0.312
P29	240	215	250	0.001	0.000	-0.001	-0.407	-0.072	-0.847	0.942	-0.001	-0.001	0.001	0.107	-0.197	0.213	0.309
P31	220	195	260	0.001	0.000	-0.001	-0.327	-0.029	-0.858	0.919	-0.001	-0.001	0.001	0.087	-0.184	0.202	0.286
P33	260	195	260	0.001	0.000	-0.001	-0.395	-0.021	-0.865	0.951	-0.001	-0.001	0.001	0.084	-0.212	0.213	0.312
P35	240	215	260	0.001	0.000	-0.001	-0.386	-0.053	-0.864	0.948	-0.001	-0.001	0.001	0.101	-0.202	0.212	0.310
P37	220	195	270	0.001	0.000	-0.001	-0.305	-0.009	-0.875	0.926	-0.001	-0.001	0.001	0.081	-0.190	0.200	0.287

Fig. 8(a-c): Position errors of the end-effector measured experimentally and determined by the shape function in the X, Y and Z directions

Fig. 9: Comparison of end-effector errors before (red) and after (blue) calibration

The graph in Fig. 9 shows the position error values of the robot in the workspace before and after compensation. In the figure, the red line represents the errors without calibration and the blue represents those with calibration.

With the calibration of the joint variable, the end-effector position accuracy was significantly improved (the average error decreased from 0.936-0.302 mm). This demonstrates the correctness and efficiency of the proposed method.

CONCLUSION

To calibrate the kinematics of robots after regular or extended periods of service, we proposed a method consisting of three steps: measurement of errors at sample poses, interpolation of errors in the survey space and compensation of errors. Interpolation of shape functions reduced the time requirement while the accuracy through tests was found to be within permitted limits. The proposed error compensation method was proven reasonable when the results after calibration showed a clear improvement in accuracy. This strategy can be applied practically in workshop conditions because it does

not affect the robot, nor require a significant amount of time to implement. The method can also be applied to many different types of robots, regardless of the number of DOF or type of workspace.

ACKNOWLEDGEMENTS

This research was supported by the Thai Nguyen University of Technology (TNUT) of Vietnam (T2019-B07 project).

REFERENCES

- Abderrahim, M., A. Khamis, S. Garrido, L. Moreno and L.K. Huat, 2006. Accuracy and Calibration Issues of Industrial Manipulators. In: *Industrial Robotics: Programming, Simulation and Applications*, Huat, L.K. (Ed.). IntechOpen, London, UK., ISBN:3-86611-286-6, pp: 131-135.
- Bai, Y. and D. Wang, 2003a. Improve the position measurement accuracy using a dynamic on-line fuzzy interpolation technique. *Proceedings of the 3rd International Workshop on Scientific use of Submarine Cables and Related Technologies*, July 31-31, 2003, IEEE, Lugano, Switzerland, pp: 227-232.
- Bai, Y. and D. Wang, 2003b. On the comparison of interpolation techniques for robotic position compensation. *Proceedings of the Joint 2003 IEEE International Conference on Systems, Man and Cybernetics SMC'03 and Theme-System Security and Assurance (Cat. No.03CH37483)* Vol. 4, October 8, 2003, IEEE, Washington, DC., USA., pp: 3384-3389.
- Bai, Y. and D. Wang, 2004. Improve the robot calibration accuracy using a dynamic online fuzzy error mapping system. *IEEE. Trans. Syst. Man Cybern. Part B.*, 34: 1155-1160.
- Bai, Y. and D. Wang, 2006. Fuzzy Logic for Robots Calibration-Using Fuzzy Interpolation Technique in Modeless Robot Calibration. In: *Advanced Fuzzy Logic Technologies in Industrial Applications*, Bai, Y., H. Zhuang and D. Wang (Eds.). Springer, London, UK., ISBN:978-1-84628-468-7, pp: 299-313.
- Bai, Y. and D. Wang, 2016. On the comparison of an interval Type-2 Fuzzy interpolation system and other interpolation methods used in industrial modeless robotic calibrations. *Proceedings of the 2016 IEEE International Conference on Computational Intelligence and Virtual Environments for Measurement Systems and Applications (CIVEMSA)*, June 27-28, 2016, IEEE, Budapest, Hungary, ISBN:978-1-4673-9760-5, pp: 1-6.
- Bai, Y. and H. Zhuang, 2004. On the comparison of model-based and modeless robotic calibration based on the fuzzy interpolation Technique. *Proceedings of the International IEEE Conference on Robotics, Automation and Mechatronics*, December 1-3, 2004, IEEE, Singapore, pp: 892-897.
- Bai, Y. and H. Zhuang, 2005. On the comparison of bilinear, cubic spline and fuzzy interpolation techniques for robotic position measurements. *IEEE. Trans. Instrum. Meas.*, 54: 2281-2288.
- Bai, Y., J.C. Smith, H. Zhuang and D. Wang, 2008. Calibration of parallel machine tools using fuzzy interpolation method. *Proceedings of the 2008 IEEE International Conference on Technologies for Practical Robot Applications*, November 10-11, 2008, IEEE, Woburn, Massachusetts, USA., ISBN:978-1-4244-2791-8, pp: 56-61.
- Borrmann, C. and J. Wollnack, 2014. Calibration of external linear robot axes using spline interpolation. *Proceedings of the 2014 International Conference on Modelling, Identification & Control*, December 3-5, 2014, IEEE, Melbourne, Australia, pp: 111-116.
- Conrad, K.L., P.S. Shiakolas and T.C. Yih, 2000. Robotic calibration issues: Accuracy, repeatability and calibration. *Proceedings of the 8th Mediterranean Conference on Control and Automation (MED2000)*, July 17-19, 2000, Rio, Patras, Greece, pp: 1-6.
- Hayati, S., K. Tso and G. Roston, 1988. Robot geometry calibration. *Proceedings of the 1988 IEEE International Conference on Robotics and Automation*, April 24-29, 1988, IEEE, Philadelphia, Pennsylvania, USA., pp: 947-951.
- Kamali, K., A. Joubair, I.A. Bonev and P. Bigras, 2016. Elasto-geometrical calibration of an industrial robot under multidirectional external loads using a laser tracker. *Proceedings of the 2016 IEEE International Conference on Robotics and Automation (ICRA)*, May 16-21, 2016, IEEE, Stockholm, Sweden, pp: 4320-4327.
- Kong, L., G. Chen, Z. Zhang and H. Wang, 2018. Kinematic calibration and investigation of the influence of universal joint errors on accuracy improvement for a 3-DOF parallel manipulator. *Rob. Comput. Integr. Manuf.*, 49: 388-397.
- Liu, Z., J. Xu, Q. Cheng, Y. Zhao, Y. Pei and C. Yang, 2018. Trajectory planning with minimum synthesis error for industrial robots using screw theory. *Intl. J. Precis. Eng. Manuf.*, 19: 183-193.
- Ma, L., P. Bazzoli, P.M. Sammons, R.G. Landers and D.A. Bristow, 2018. Modeling and calibration of high-order joint-dependent kinematic errors for industrial robots. *Rob. Comput. Integr. Manuf.*, 50: 153-167.

- Mooring, B.W., Z.S. Roth and M.R. Driels, 1991. Fundamentals of Manipulator Calibration. Wiley, New York, USA., ISBN:9780471508649, Pages: 329.
- Sun, T., Y. Zhai, Y. Song and J. Zhang, 2016. Kinematic calibration of a 3-DoF rotational parallel manipulator using laser tracker. Rob. Comput. Integr. Manuf., 41: 78-91.
- Wang, D., Y. Bai and J. Zhao, 2012. Robot manipulator calibration using neural network and a camera-based measurement system. Trans. Inst. Meas. Control, 34: 105-121.
- Wang, S.M., Y.L. Liu and Y. Kang, 2002. An efficient error compensation system for CNC multi-axis machines. Intl. J. Mach. Tools Manuf., 42: 1235-1245.
- Weill, R. and B. Shani, 1991. Assessment of accuracy of robots in relation with geometrical tolerances in robot links. CIRP. Annals, 40: 395-399.
- Yu, C. and J. Xi, 2018. Simultaneous and on-line calibration of a robot-based inspecting system. Rob. Comput. Integr. Manuf., 49: 349-360.