

<http://www.pjbs.org>

**PJBS**

ISSN 1028-8880

**Pakistan  
Journal of Biological Sciences**

**ANSI***net*

Asian Network for Scientific Information  
308 Lasani Town, Sargodha Road, Faisalabad - Pakistan

## Determination of Carbon/Nitrogen Ratio and Heavy Metals in Bulking Agents Used for Sewage Composting

<sup>1</sup>H. Alidadi, <sup>1</sup>A.A. Najafpoor and <sup>2</sup>A. Parvaresh  
<sup>1</sup>Department of Environmental Health, Faculty of Health,  
Mashhad University of Medical Sciences, Iran  
<sup>2</sup>Department of Environmental Health, Faculty of Public Health,  
Isfahan University of Medical Sciences, Iran

**Abstract:** Improving the soil quality with organic matter and N, P and K contents are some of sewage sludge benefits. Adjusting carbonaceous materials such as plant wastes to dewatered sludge compost results in increasing the moisture content and improving C/N ratio. This study was conducted for three months in 2005, in Laboratory of Chemistry of Water and Wastewater in the School of Public Health of Isfahan University of Medical Science, to determine the C/N ratio and heavy metals concentration of bulking agents in sawdust, leaves, rice hulls and dewatered sewage sludge. Dewatered sludge was collected from Isfahan sewage treatment plant. Sawdust was collected from sawmills. Leaves were collected from municipality of Isfahan and rice hull from rice mills, then in samples determined C/N ratio and heavy metal according to standard methods. The results showed that concentrations of chromium and cadmium in the mixture of dewatered sewage sludge and bulking agents were lower than those of the standard level. Means of cobalt ( $115.44 \text{ mg kg}^{-1}$ ), nickel ( $57.44 \text{ mg kg}^{-1}$ ) and zinc ( $273.48 \text{ mg kg}^{-1}$ ) concentrations were maximum in dewatered sludge but mean concentration of cobalt ( $25.66 \text{ mg kg}^{-1}$ ) in rice hull samples and mean zinc ( $8.99 \text{ mg kg}^{-1}$ ) and nickel ( $5.106 \text{ mg kg}^{-1}$ ) concentrations in sawdust samples were minimum. The optimal conditions sewage sludge composting, each kilogram of sludge needs 350 g of saw dust, 470 g of leaves and 388 g of rice hull. Amount of heavy metals present in the bulking agents is lower than the amount mentioned for the compost.

**Key words:** Bulking agents, dewatered sludge, C/N ratio, heavy metals

### INTRODUCTION

Agricultural and horticultural production process, a proportion of raw or final product is wasted (e.g., straw from corn, roots and leaves from vegetables). In most cases, the wastes remain in the production site, become part of the organic matter and subjected to the degradation and rotting processes by macro and microorganisms (field composting). In some cases, these wastes are collected, as they are valuable. In addition, carbon compounds used to the soil can cause nitrogen immobilization and so additional nitrogen fertilizing is required (Tisdale and Nelson, 2001).

The use of dewatered sewage sludge in agriculture has many benefits. Organic matter content improves the soil structure while the presence of nutrients such as N, P and K it as increases soil fertility. Hence, this substance is composted and it as used for agricultural purposes and be a substitute for expensive inorganic fertilizers.

Presence of pathogens and content of heavy metals are limitations in using sludge compost for agricultural purposes (Rehm and Reed, 2000). Windrow is the most common method of sludge composting, in which dewatered sludge is mixed with bulking agents. Successful compost stabilization process of dewatered sludge depends on maintaining a suitable environment for process control including moisture content, oxygen concentration, carbon-nitrogen ratio, temperature, pH and macro and micronutrients.

Adjusting carbonaceous materials (plant wastes) to dewatered sludge compost increases its moisture content, improves the aeration and C/N ratio. Since dewatered sludge has a low C/N ratio and mixing, it with bulking agents adjusts its C/N ratio. In addition, dewatered sludge is often too wet and adjusting of dry bulking materials to absorb its surplus moisture increases its porosity (Lopez and Medejon, 2001). A biodegradable carbon-nitrogen (C/N) weight ratio of 25 to 35 has been

found to provide optimal conditions for compost process. Lower C/N ratio increases the loss of nitrogen by leaching (e.g., nitrate mobilization) and ammonia volatilization, whereas higher levels necessitate progressively longer composting time as nitrogen becomes the microbial limiting nutrient. Sludge normally has C/N ratios in range of 10 to 20. To offset an imbalance in the C/N ratio, compost amendments usually are necessary. Typical compost amendments include materials with high C/N ratio such as Sawdust, leaves, wood chips, rice hulls and old compost.

Dewatered sewage sludge composting with bulking agents converts it into a useful product. Land application of sewage sludge compost is restricted due to its content of heavy metals, pathogens and persistence of organic pollutants in the sludge (Tchobanoglous and Theisen, 2001). The major nutrient elements or macronutrients in the compost include carbon, nitrogen, phosphorous and potassium. The micronutrient elements mostly used are cobalt, manganese, magnesium, copper and zinc. Micronutrients are essential for the growth and development of microorganisms, zinc and copper are essential for many microorganisms in the compost while toxic metals are not. Toxic metals include chromium and cadmium, etc. Plants easily take up cadmium; it is highly bioavailability for plant uptake. Mixing dewatered sewage sludge by adding the bulking agents decrease the toxicity content (Pescod, 2000). In this study C/N ratio and heavy metal contents of bulking agents such as sawdust, leaves, rice hulls and dewatered sewage sludge were assessed, to use these informations in sewage sludge composting.

**MATERIALS AND METHODS**

This study was performed during a three month period from June to August 2005, in Laboratory of Chemistry of Water and Wastewater in the School of Public Health, Isfahan University of Medical Science,

Iran. Dewatered sludge was collected from Isfahan Sewage Treatment Plant. Sawdust was collected from sawmills. Leaves were collected from municipality of Isfahan and rice hull from rice mills. Samples were obtained three times per week and then were transferred to the Laboratory for conducting various tests according to standard methods (APHA, AWWA, WPCF, 2000). Fifteen and twenty tests were conducted to determine C/N ratio and heavy metal analysis, respectively. Total carbon content of the samples determined through combustion in ovens at 750°C for 2 h. Total nitrogen analysis was performed by Kjeldahl method. Samples were digested by nitric acid 1+1 and heavy metals contain Cr, Cd, Zn, Ni and Co analyzed by flame atomic absorption (Theroux and Eldridge, 2002).

**RESULTS AND DISCUSSION**

This study showed that sufficient amounts of nitrogen and trace elements (cobalt, zinc and nickel) are found in dewatered sludge, but, its carbon content is low; for adjusting its C/N ratio it should be mixed up with amendment agents and so leaves, rice hull and saw dust should be added to dewatered sludge used for composting. According to Table 1, the mean of C/N ratio in the leaves, saw dust and dewatered sludge is similar to that of obtained by Warman and Termee (2000) and Jones (2002). This study showed that dewatered sludge contained harmful toxic metals (chromium and cadmium). These metals kill the microorganisms of the compost and prolong the composting time. Thus mixing dewatered sludge with bulking agents decrease the concentration of toxic metals. According to Table 2, the mean of chromium, zinc and nickel in the leaves, saw dust and dewatered sludge is the same as Kreith (2002) findings. If optimum C/N ratio for sewage sludge composting considers 25, in optimal conditions, 350 g of sawdust, 470 g of leaves plus 388 g of rice hull should be added to each kilogram of sludge for composting which Gibbs and Hu (2000) appreciates.

Table 1: Amounts of carbon and nitrogen percentage and C/N ratio in different materials

| Samples          | No. of samples | Mean of carbon (%) | Mean of nitrogen (%) | Mean of C/N  |
|------------------|----------------|--------------------|----------------------|--------------|
| Dewatered sludge | 15             | 20.380±2.485       | 1.3490±0.3190        | 15.83±3.568  |
| Leaves           | 15             | 41.480±1.270       | 0.6760±0.1420        | 63.92±13.51  |
| Rice hull        | 15             | 39.205±0.908       | 0.3388±0.0587        | 119.43±22.43 |
| Sawdust          | 15             | 37.470±1.390       | 0.1250±0.0240        | 310.51±66.20 |

Table 2: Amounts of carbon and nitrogen percentage and C/N ratio in different materials

| Samples          | No. of samples | Chromium                    | Cadmium       | Nickel       | Zinc            | Cobalt         |
|------------------|----------------|-----------------------------|---------------|--------------|-----------------|----------------|
|                  |                | Mean (mg kg <sup>-1</sup> ) |               |              |                 |                |
| Dewatered sludge | 20             | 167.520±50.100              | 19.470±11.734 | 57.439±5.807 | 273.484±101.532 | 115.440±52.890 |
| Leaves           | 20             | 105.000±36.196              | 4.159±4.8300  | 17.441±4.839 | 47.353±28.231   | 41.445±35.707  |
| Rice hull        | 20             | 43.720±24.970               | 3.890±3.9900  | 8.614±4.842  | 23.740±8.8590   | 25.660±31.870  |
| Sawdust          | 20             | 56.925±29.887               | 2.109±3.5660  | 5.106±2.263  | 8.987±3.5690    | 36.879±41.568  |

This study showed that the amount of heavy metals present in the bulking agents was lower than that of the compost, also each kilogram of sludge for composting needs additional for 350 g of sawdust, 470 g of leaves and 388 g of rice hull.

#### **ACKNOWLEDGMENTS**

We would like to express our thanks to M. Moosavi for his cooperation to perform this research study and Mrs. Marzieh Vahid, Researcher of Environmental Laboratory, for her helps in this study.

#### **REFERENCES**

- APHA, AWWA and WPCF, 2000. Standard Methods for the Examination of Water and Wastewater. 18th Edn., New York.
- Gibbs, R.A. and C.J. Hu, 2000. Giardia and its implications for sludge disposal. *Wat. Sci. Technol.*, 34: 179-86.
- Johns, A., 2002. Agricultural Use of Organic Wastes. 2nd Edn., McGraw-Hill, New York.
- Kreith, F., 2002. Handbook of Solid Waste Management. McGraw-Hill, New York.
- Lopez, R. and E. Medejon, 2001. Co-composting of sugar beet vinasse influence of the organic matter nature of the bulking agents used. *Bioresour. Technol.*, 76: 275-278.
- Pescod, M.B., 2000. Treatment and Use of Sewage Effluent for Irrigation. Published by FAO.
- Rehm, H.J. and G. Reed, 2000. Biotechnology. 2nd Edn., John Wiley Company Inc., New York.
- Tchobanoglous, G. and H. Theisen, 2001. Integrated Solid Waste Management. 2nd Edn., McGraw-Hill, New York.
- Theroux, F. and E. Eldridge, 2002. Laboratory Manual for Chemical and Bacterial Analysis of Water and Sewage. McGraw-Hill, New York.
- Tisdale, S.L. and W.L. Nelson, 2001. Soil Fertility and Fertilizers. McGraw-Hill Inc., New York.
- Warman, P.R. and W.C. Termee, 2000. Composting and evaluation of race track manure, grass clipping and sewage sludge. *Bioresour. Technol.*, 55: 95-101.